

जीवाजी विश्वविद्यालय, ग्वालियर

क्रमांक/ एफ.जे.यू./स्टोर/2022/10

दिनांक: - 13/01/2022

प्रति,

.....
.....
.....

विषय : - जीवाजी विश्वविद्यालय परिसर में सुरक्षा पहरियों के लिये 06 हट्स बनाये जाने का कार्य कराये जाने बावत्

महोदय,

उपरोक्त विषय के संदर्भ में सूचित किया जाता है। कि जीवाजी विश्वविद्यालय परिसर में सुरक्षा पहरियों के लिये 06 हट्स बनाये जाने है। इस संबंध में लिफाफे के ऊपर (जीवाजी विश्वविद्यालय परिसर में सुरक्षा पहरियों के लिये हट्स) का नाम अंकित कर कुलसचिव जीवाजी विश्वविद्यालय, ग्वालियर के नाम कुटेशन दिनांक 28-01-2022 तक स्पीड पोस्ट से आमंत्रित किये जायेंगे।

| सं. क्र. | एस.ओ. आर. क्रमांक | विवरण | मात्रा | दर |
|----------|-------------------|--|---------------|----|
| 01. | 10.2 | Structural steel work using M.S. flats, angles, channels I-section, H-section etc. riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete | 158.87 k.g | |
| 02. | 12.15 | Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm + 0.05 %, total coated thickness with zinc coating 120gsm as per IS: 277 in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self-drilling /self-tapping screws of size (5.5x 55mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. | 15.96 sqm | |
| 03. | 12.16.1 | Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 0.05 % total coated thickness, Zinc coating 120gsm as per IS: 277 in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the | 1.04 sqm | |

| | | | | |
|-----|--------|---|-------|-----|
| | | sheet and polyester top coat 15-18 microns using self-drilling/ self-tapping screws complete | | |
| 04. | 13.57 | Painting on G.S. sheet with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: New work (two or more coats) including a coat of approved steel primer but excluding a coat of mordant solution. | 38.64 | sqm |
| 05. | 9.17.2 | Providing and fixing Pre-laminated flat pressed 3 layer (medium density) particle board or graded wood particle board IS : 3087 marked with one side decorative and other side balancing lamination Grade I, Type II exterior grade IS : 12823 marked in shelves with screws and fittings wherever required, edges to be painted with polyurethane primer (fittings to be paid separately). 25 mm thick | 2.87 | sqm |


कुलसचिव

प्रतिलिपि :-

- 1- श्रीमान संजय बरथरिया की ओर वेबसाइट पर अपलोड करने हेतु प्रस्तुत है।


सहा-कुलसचिव स्टोर