

# जीवाजी विश्वविद्यालय, ग्वालियर

## कोटेशन आमंत्रण पत्र

क्रमांक/ एफ.जे.यू./यंत्रि/2022/ 146

दिनांक: - 01/08/2022

प्रति,

विषय : - जी.वि.वि.के प्रशासन भवन, छात्र सहायता, केन्द्र सी-ब्लॉक मे एल्युमीनियम दरवाजे,ग्रिल एवं रेम्प कार्य करायें जाने बावत् ।

महोदय,

जी.वि.वि.के प्रशासन भवन, छात्र सहायता केन्द्र सी-ब्लॉक मे एल्युमीनियम दरवाजे,ग्रिल एवं रेम्प कार्य करायें हेतु दरें आमंत्रित की जाती है। कृपया आप अपनी दरें एम.पी. पी.डब्लू. एस.ओ.आर. विधुत कार्य की दरों पर प्रतिशत कम पर दिनांक...16/08/2022...सायं 5:00 बजे तक सील बंद लिफाफे मे स्पीडपोस्ट/पंजीकृत डाक के माध्यम से कुलसचिव जीवाजी विश्वविद्यालय ग्वालियर के पते पर भेंजे। लिफाफे पर कुटेशन, कार्य का नाम तथा अंतिम तिथि आवश्यक रूप से अंकित करें,

S. N. /	Desprication	Qty	Rate	Amount
01.	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : Powder coated aluminium (minimum thickness of powder coating 50 micron	4.86 Kg.		
02.	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item) : With float glass panes of 5.0 mm thickness (weight not less than 12.50 kg/sqm )	1.14 sqm		
03.	Providing and fixing 12 mm thick frameless toughened glass door shutter of approved brand and manufacture, including providing and fixing top &	25.28 sqm		

	bottom pivot & double action hydraulic floor spring type fixing arrangement and making necessary holes etc. for fixing required door fittings, all complete as per direction of Engineer-in-Charge (Door handle, lock and stopper etc.to be paid separately).			
04.	Brick work with well burnt chimney bricks in bulls pattern trench kiln, crushing strength not less than 25kg /cm <sup>2</sup> and water absorption not more than 20% in superstructure above plinth level and up to floor two level i/c curing etc complete. Cement Mortar 1:6 (1 cement:6 sand).	0.74 cum		
05.	Cement Mortar 1:6 (1 cement:6 sand). 1:6 (1 cement : 6 sand)	5.11 sqm		
06.	Providing and fixing on wall face Rigid Unplasticised rigid PVC (upvc) Single socketed rain water pipes conforming to IS : 13592 Type A including jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion 110 mm diameter (minimum wall thickness 2.2mm)	31.40 sqm		
07.	Providing and fixing on wall face Unplasticised - UPVC moulded fittings/ accessories for Unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A including jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion 110x110x110 mm (minimum wall thickness 2.2mm)	06 Nos.		
08.	Dismantling tile/ Kota stone/ Marble / Granite work in floors/walls and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm.	4.32 sqm		
09.	Steel work in built up M.S. tubular section (round, square or rectangular hollow tubes etc.) trusses/frame work etc. including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished welded type tubes	93.84 Kg.		
10.	Providing and laying vitrified floor tiles Multi/Double charged (Minimum top layer thickness 2.0mm) Neno Polished self design, in different size with water absorption less than 0.05% and conforming to IS:15622 of approved make in all colours& shades, quality/ premium quality in flooring laid on 12mm thick cement mortar 1:4(1cement :4sand) including grouting the joints with white cement and matching pigments etc. complete Size 600X600 mm thickness 9-10 mm	4.32 sqm		
11.	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm + 0.05 %, total coated thickness with zinc coating 120 gsm as per IS: 277 in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat	6.37 sqm		

	15-18 microns. Sheet should have protective guard film. of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self-drilling /self-tapping screws of size (5.5x 55mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required			
12.	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with flat iron diagonals 20x5mm size with top and bottom rail of T-iron 40x40x6mm with 40mm dia steel pulleys complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer. Rate includes recess cutting in floor and making good the same wherever required	17.27 sqm		
13.	Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In stringers, treads, landings etc. of stair cases including use of chequered plate wherever required, all complete	301.34 kg		
14.	Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified. 2mm thick flat.	3.24 sqm		
15.	Providing half brick masonry with well burnt chimney bricks in bull pattern trench kiln crushing strength not less than 25 kg /cm <sup>2</sup> and water absorption not more than 20% in superstructure above plinth level and up to floor two level Cement mortar 1:4 (1 cement : 4 sand)	1.46 sqm		
16.	Supplying and filling in plinth with crusher stone dust / coarse sand under floors including, watering, ramming and compacting in layers not exceeding 20cm in depth and dressing complete <b>Note:</b> - Maximum thickness of this layer shall be 20 cm.	1.42 cum		
17.	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work upto plinth level : M-15 – Grade concrete	0.78 cum		

18.	Providing and laying Ceramic glazed floor tiles 300x300 mm or more (having thickness 6 to 7mm) of 1st quality conforming to IS : 15622 of approved make in any colours and shade laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 sand) including pointing the joints with white cement and matching pigment etc., complete.	10.32 sqm		
19.	Wall painting by any mechanical or manual means with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats.	204.11 sqm		

शर्त :-

1. सामग्री की मात्रा आवश्यकतानुसार घटाई व बढ़ाई जा सकती है।
2. फर्म के नाम पैन नम्बर/टिन नम्बर/जी.एस.टी.नम्बर होना आवश्यक है।
3. कुटेशन स्वीकृत/अस्वीकृत करने का अधिकार कुलसचिव विश्वविद्यालय के पास सुरक्षित रहेगा।
4. कुटेशन अंतिम तिथि तक वि.वि. में रजिस्टर्ड डाक से प्राप्त हो जाने चाहिये।

  
कुलसचिव

प्रतिलिपि :-

1. श्रीमान संजय बरथरिया की ओर वेबसाइट पर अपलोड करने हेतु प्रस्तुत है।

  
वि.वि.यंत्री