

online

जीवाजी विश्वविद्यालय, ग्वालियर

कोटेशन आमंत्रण पत्र

क्रमांक/ एफ.जे.यू./यंत्रि/2022/1069

दिनांक: - 18/04/2022

प्रति,

.....
.....
.....

विषय : - जीवाजी विश्वविद्यालय के परीक्षा भवन में टॉयलेट में सेनेट्री कार्य बावत् ।

महोदय,

जीवाजी विश्वविद्यालय के परीक्षा भवन में टॉयलेट में सेनेट्री कार्य कराये जाने हेतु दरें आमंत्रित की जाती है। कृपया आप अपनी दरें दिनांक 02/5/2022 सायं 5:00 बजे तक सील बंद लिफाफे में स्पीडपोस्ट/पंजीकृत डाक के माध्यम से कुलसचिव जीवाजी विश्वविद्यालय ग्वालियर के पते पर भेजें। लिफाफे पर कुटेशन, कार्य का नाम तथा अंतिम तिथि आवश्यक रूप से अंकित करें,

S. N. / SOR No.	Desprication	Qty	Rate	Amount
01./9.109.2	Providing and fixing aluminium sliding door bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with nuts and screws etc. complete: 250x16 mm	02 Nos.		
02./110.3	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete: 250x10 mm	02 Nos.		
03./113.1	Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete: 125 mm	04 Nos.		
04./9.158.1	Providing and fixing factory made UPVC door frame made of UPVC extruded sections having an overall dimension as below (tolerance ± 1 mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws, joints mitred and Plastic welded. The hinge side vertical of the frame reinforced	5.30 mtr		



	<p>by galvanized M.S. tube of size 19 X 19mm and 1mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturers specification and direction of Engineer-in-charge: Extruded section Profile size 48x40 mm.</p>			
05./9.159	<p>Providing and fixing Panelled UPVC door shutter to existing door frames. 24 mm thick factory made UPVC door shutters made of styles and rails of a UPVC hollow section of size 59x24 mm and wall thickness 2 mm (± 0.2 mm) with inbuilt edging on both sides. The styles and rails mitred and joint at the corners by means of M.S. galvanised/plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 20x20 mm and 1 mm (± 0.1 mm) wall thickness. The lock rail made up of a UPVC hollow 'H' section, section of size 100x24 mm and 2 mm (± 0.2 mm) wall thickness, fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a UPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (± 0.1 mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge. (For W.C. and bathroom door shutter).</p>	4.20 sqm		
06./11.48	<p>Providing and laying Ceramic glazed floor tiles 300x300 mm or more (having thickness 6 to 7mm) of 1st quality conforming to IS : 15622 of approved make in any colours and shade laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 sand) including pointing the joints with white cement and matching pigment etc., complete</p>	10.59 sqm		
07./11.49	<p>Providing and fixing Ceramic glazed wall tiles 300x450 mm or more (having thickness 6 to 7 mm) of 1st quality conforming to IS: 15622 of approved make in all Colours& shades, except burgundy, bottle green, black laid on 12mm thick bed of Cement Mortar 1:3 (1 Cement: 3 sand)prepad same day when mortar is still green jointed with grey cement slurry @3.3 kg per sqm including pointing the joints with white cement and matching pigments etc., complete</p>	17.63 sqm		
08./15.11.1	<p>Dismantling tile/ Kota stone/ Marble / Granite work in floors/walls and roofs laid in cement mortar including stacking material within 50 metres lead.</p>	28.22 sqm		

	For thickness of tiles 10 mm to 25 mm.			
09./17.2.1	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete including cutting and making good the walls and floors wherever required : W.C. pan with ISI marked white solid plastic seat and lid	04 Nos.		
10./17.22.1	Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. 10 litre capacity White	24 Nos.		
11./17.24.1	Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete : White	06 Nos.		
12./17.64.1.2	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. 40 mm dia	02 Nos.		
13./17.71	Providing and fixing CP brass waste coupling of approved quality and make for sink and wash basin Waste coupling 31mm of 79mm length and 62mm breadth	02 Nos.		
14./18.6.1.1	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot and cold water supply including all CPVC plain and brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-Charge (i) 5 mm nominal outer dia .Pipes. (ii) 32 mm nominal outer dia .Pipes.	7.20 mtr 4.50 mtr		
15./18.14.1	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete 15 mm nominal bore	01 Nos.		
16./18.37	Providing and fixing C.P. brass pillar cock approved quality and make conforming to IS: specification. 15 mm nominal bore 125 mm long foam flow.	05 Nos.		
17./18.44.2	Providing and fixing PTMT bib cock of approved quality and colour 15mm nominal bore. 122 mm long weighing not less than 99 gm	24 Nos.		
18./18.45.2	Providing and fixing PTMT stop cock of approved quality and colour. 20mm nominal bore, 89mm long. Weighing not less than 88 gms.	30 Nos.		
19./18.46.2	Providing and fixing PTMT pillar cock of approved quality and colour	14 Nos.		

[Handwritten signature]

	15mm nominal bore, 125mm long foam flow weighing not less than 120 gms.			
20./18.52.2	Providing and fixing Unplasticised P.V.C. connection pipe with PTMT Nuts collar and bush of approved quality and colour 15 mm nominal bore	57 Nos.		


शर्तें :-

1. सामग्री की मात्रा आवश्यकतानुसार घटाई व बढ़ाई जा सकती है।
2. फर्म के नाम पैन नम्बर/टिन नम्बर/जी.एस.टी.नम्बर होना आवश्यक है।
3. कुटेशन स्वीकृत/अस्वीकृत करने का अधिकार कुलसचिव विश्वविद्यालय के पास सुरक्षित रहेगा।
4. कुटेशन अंतिम तिथि तक वि.वि. में रजिस्टर्ड डाक से प्राप्त हो जाने चाहिये।


कुलसचिव

प्रतिलिपि :-

1. श्रीमान संजय बरथरिया की ओर वेबसाइट पर अपलोड करने हेतु प्रस्तुत है।


वि.वि. प्रिन्सीपल